


# Expand your working capacity Trackita

Thakita





165mm<sub>(6-1/2")</sub> 305mm<sub>(12")</sub>

Maximum height

**Throat width** 

#### LED job light switch

#### Anti-restart function

(for countries where regulations require it) prevents accidental startup for safety even if the machine is plugged to power source with the switch on.

#### Easy-to-Read Scale

with large graduations and magnifying lens.



# Wheeled stand for easier mobility

Stand with two caster wheels and a lifting handle adds mobility for convenient repositioning of the machine.



#### Quick-release tension lever for tool-less easy blade change allows to easily loosen or

tighten the band saw blade without using tools.

#### **LED** job light

6 LEDs illuminate working surface for easier cutting in dark places.



#### **Bevel cutting**

base can be tilted up to 45-degrees.



#### **Easy connecting** with vacuum cleaner

Both 63mm and 100mm hoses can be connected.




#### High / Low speed selection for excellent

results in both hard and soft wood



## Accessories

Band saw blade Thickness: 0.5 mm



Width	No. of teeth per inch	Application	Part No.	
16mm	4	Wood/ for cross-cut	B-16667	
13mm	4	Wood/ for universal	B-16673	
6mm	6	Wood/ for curve-cut	B-16689	
16mm	14	Nonferrous metal	B-16695	

#### **Extension table set**

Part No. JM21000300

**Dust box** 

keeps the work place clean.



### Circular cutting attachment set



#### **Belt sanding attachment set**

Part No. JM21000330



Use a sanding belt that is 2240 mm long and 20 mm wide or less.

# **Band Saw**



**Mechanical 2-speed** 



**Built-in job light** 



**Dust collecting** 

#### **LB1200F**

**Continuous rating Input** 

Thickness of cut: 165mm (6-1/2") Throat: 305mm (12") Capacity Hi: (50Hz) 800m (60Hz) 1,000m/min. Lo: (50Hz) 400m (60Hz) 500m/min. Blade speed

615 x 775 x 1,600mm (24-1/4" x 30-1/2" x 63") Dimensions(LxWxH)

Net weight 81.2kg (179.0lbs)

Power supply cord 2.5m (8.2ft)

Standard Equipment Band Saw Blades, Rip Fence, Angle Rule, Push Stick 2, Nozzle 93, Band Saw Stand, Hex Wrenches

\*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area

# **Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan