## Grounding Busbar – EGBA14436CC



Proper bonding is essential to create an equipotential plane between service grounds and equipment during fault and transient conditions. This equipotential plane provides a near-zero voltage differential, and serves to protect people and equipment during these events. The grounding busbar is the most popular bonding product in use today.

- Provides a convenient, single-point grounding and bonding location
- Conductors are welded to the bar using a nVent ERICO Cadweld exothermic connection or are mechanically fastened by using ٠ lugs
- Custom bars can be designed and manufactured to customer specifications

			3/4" [ 19.1 ]		
0	-0 0 0	000	0000		0
	-	- 2	"[50.8]	1"[25.4	]



Part Number	EGBA14436CC	
Material	Copper	
Busbar Configuration	Busbar, Insulators and Brackets	
Hole Pattern	CC	
Mounting Hole Size	11.1 mm	
Length	914 mm	
Width	102 mm	
Thickness	6.4 mm	
Tin Plating	No	
Pigtail Included	No	
Certifications	cULus	
Standard Packaging Quantity	1 рс	
UPC	78285644573	
EAN-13	8711893152838	

Diagrams are representative of the hole pattern. The number of holes is dependent on the length of the grounding busbar.





UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

