


Non-Insulated Solid Conductor – RSCC4SS1050 (197696)



- Solid cable for a variety of applications
- Available in smaller spool sizes for convenience
- LPA and LPC parts are used for lightning protection system downconductor or grounding applications



Part Number	RSCC4SS1050
Article Number	197696
Material	Stainless Steel 316L (EN 1.4404)
Finish	Bare
Conductor Size	3/0 Solid
Cross Section	78.6 mm ²
Diameter (Ø)	10 mm
Length (L)	50 m
Unit Weight	0.63 kg
Standard Packaging Quantity	50 m
UPC	78285693971
EAN-13	0782856939719

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent. All rights reserved.

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.