


# Non-Insulated Solid Conductor – RSCC850 (197679)



- Solid cable for a variety of applications
- Available in smaller spool sizes for convenience
- LPA and LPC parts are used for lightning protection system downconductor or grounding applications



Part Number	RSCC850
Article Number	197679
Material	Steel
Finish	Hot-Dip Galvanized
Conductor Size	1/0 Solid
Cross Section	50.3 mm <sup>2</sup>
Diameter (Ø)	8 mm
Length (L)	50 m
Unit Weight	0.4 kg
Standard Packaging Quantity	50 m
UPC	78285693954
EAN-13	0782856939542

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent. All rights reserved.

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.