Non-Insulated Solid Conductor - RSCCA1330 (197705)



- Solid cable for a variety of applications
- Available in smaller spool sizes for convenience
- LPA and LPC parts are used for lightning protection system downconductor or grounding applications



Part Number	RSCCA1330
Article Number	197705
Material	Aluminum
Finish	Bare
Conductor Size	5/0 Solid
Cross Section	132.7 mm²
Diameter (Ø)	13 mm
Length (L)	30 m
Unit Weight	0.359 kg
Standard Packaging Quantity	30 m
UPC	78285693976
EAN-13	0782856939764

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

 \odot 2019 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

