



PVC Covered Aluminium Tape




Reference code	Part No.	Width A mm	Thick B mm	Colours	Unit weight kg
ATBL253	710750	25	3	Black	0,30/m
ATBN253	710760	25	3	Brown	0,30/m
ATGY253	710770	25	3	Grey	0,30/m
ATST253	710780	25	3	Stone	0,30/m
ATWH253	710790	25	3	White	0,30/m

Bare Galvanised Steel Tape




Reference code	Part No.	Width A mm	Thick B mm	Unit weight kg
30TCHGSP3035	197810	30	3,5	0,82/m

Bare Aluminium Round Conductor




Reference code	Part No.	Cross-section mm²	D ø mm	Unit weight kg
RAW8	198250	50,3	8	0,14/m
ASCO8	711530	50,3	8	0,14/m

PVC Covered Aluminium Round Conductor




Reference code	Part No.	Cross-section mm²	D ø mm	Colours	Unit weight kg
SABL	710840	50,3	8	Black	0,18/m
SABN	710850	50,3	8	Brown	0,18/m
SAGY	710860	50,3	8	Grey	0,18/m
SAST	710870	50,3	8	Stone	0,18/m

Bare Galvanised Round Conductor




Reference code	Part No.	Cross-section mm²	D ø mm	Unit weight kg
RSCC8	197860	50,3	8	0,400/m
RSCC10	197870	78,5	10	0,630/m


Theft Deterrent Composite Cable




CC5A04




CC5A05



CC5A20



CC5A30




CC5A40

Reference Code	Part No.	Description	Outside Diameter	Fusing Capacity Equivalency	Unit weight kg
CC5A04	CC5A04	(1) Tinned Copper, (6) Galvanised Steel Strands	8.38 mm	100% of 16 mm²	25,9
CC5A05	CC5A05	(3) Tinned Copper, (16) Galvanised Steel Strands	8.48 mm	100% of 16 mm²	26,3
CC5A20	CC5A20	(133) Tinned Copper, (21) Galvanised Steel Strands	13.36 mm	100% of >50 mm²	49,4
CC5A30	CC5A30	(133) Tinned Copper, (24) Galvanised Steel Strands	14.53 mm	100% of 70 mm²	61,2
CC5A40	CC5A40	(133) Tinned Copper, (28) Galvanised Steel Strands	16.67 mm	100% of >95 mm²	78,0

*Weight does not include reel.

Copper-bonded Steel Round Conductor



CC5A04

Reference Code	Part No.	Description	Outside Diameter	Unit weight kg
CSC8A70	CSC8A70	Copper-bonded Steel Wire	8 mm	0,410/m