



Replacement Module for DSD, 60 kA – DSD1601SR275M



Part Number	DSD1601SR275M
Nominal System Voltage (Un)	220 - 240 V
Max Continuous Operating Voltage (Uc)	275 VAC 350 VDC
Nominal Discharge Current (In), Per Mode	25 kA 8/20 μ s
Max Discharge Current (Imax), Per Mode	60 kA 8/20 μ s
Voltage Protection Level (Up)	850 V @ 3 kA 1,500 V @ 25 kA
Impulse Current (Iimp)	5 kA 10/350 μ s
Frequency	0 – 60 Hz
Short Circuit Current Rating (SCCR)	25 kA
Technology	MOV with thermal disconnect
Enclosure Material	UL® 94V-0 Thermoplastic
Status Indication	Mechanical flag
Temperature	-40 to 176 °F
Module Width	1 M
Depth (D)	1.91"
Height (H)	1.78"
Width (W)	0.71"
Unit Weight	0.1 lb
Certifications	CE Qualifoudre
Standard Packaging Quantity	1 pc
UPC	78285647247
EAN-13	8711893014419

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.