



## Ground Rod Clamp, Rod to Conductor, Stainless Steel – SP58 (158185)



- Unique stamped body design will not crack from excessive torque
- Provides a greater surface area contact to allow improved performance of the connector
- Compatible with copper, copper bonded, galvanized, stainless steel, rebar and plain steel ground rods and electrodes



Part Number	SP58
Article Number	158185
Material	Stainless Steel 304 (EN 1.4301)
Torque (TQ)	16.9 to 33.9 N-m
Ground Rod Diameter, Nominal	1/2" – 5/8"
Ground Rod Diameter, Actual (Ø)	12.7 – 15.9 mm
Conductor Size	#10 Stranded - #2 Stranded 6 mm <sup>2</sup> Stranded - 25 mm <sup>2</sup> Stranded
Wrench Size	1/2"
Certifications	cULus Qualifoudre
Standard Packaging Quantity	50 pc
UPC	78285660651
EAN-13	8711893094015

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.