

Description and characteristics

- Nylon Ties.
- For tying cables and conduits.
- High tensile strength.
- Indoor / outdoor use.
- Dimensional stability: from -40°C to + 85 °C.
- Certificación UL.
- Halogen Free material [POLYAMIDE 6].
- Black Nylon UVE resistant.

References

DIMENSIONS [mm]	WHITE	BLACK
2,5 x 100	BR25100	BR25100N
2,5 x 200		BR25200N
2,5 x 260	BR25260	BR25260N
3,6 x 140	BR36140	BR36140N
3,6 x 200	BR36200	BR36200N
3,6 x 300	BR36300	BR36300N
3,6 x 370	BR36370	BR36370N
4,8 x 200	BR48200	BR48200N
4,8 x 250	BR48250	BR48250N
4,8 x 300	BR48300	BR48300N
4,8 x 360	BR48360	BR48360N
7,6 x 150	BR76150	BR76150N
7,6 x 365	BR76365	BR76365N
7,6 x 450	BR76450	BR76450N
7,6 x 500	BR76500	BR76500N
7,6 x 550	BR76550	BR76550N
9.4 x 500		BR94500N



*Other colors:

BR48200G (Grey) // BR48250V (Green)
BR48300G (Grey) // BR48250M (Brown)

Specifications

- Directive 2014/35/UE
- EN 62 275

Technical Data

- Fire resistance (Glow Wire Test 850°C)
- Dimensional stability: -40° C to 85 ° C
- HALOGEN FREE material

