

WKRETY DWUGWINTOWE (WK)


Zabezpieczenie antykorozyjne: ocynk galwaniczny.

Gwint M	Średnica D [mm]	Długość L [mm]	Długość gwintu A [mm]	Masa [kg]	Ilość [szt./opak.]	Oznaczenie do zamówienia	Numer katalogowy
M8	8	80	28	0,02	50	WK-8X80	81460008080
M8	8	100	45	0,02	50	WK-8X100	81460008100
M8	8	120	50	0,03	25	WK-8X120	81460008120
M8	8	140	50	0,04	25	WK-8X140	81460008140
M8	8	160	50	0,05	25	WK-8X160	81460008160
M8	8	200	50	0,06	25	WK-8X200	81460008200
M10	10	100	30	0,05	10/25	WK-10X100	81460010100
M10	10	120	45	0,05	25	WK-10X120	81460010120
M10	10	140	45	0,06	25	WK-10X140	81460010140
M10	10	160	50	0,06	25	WK-10X160	81460010160
M10	10	180	45	0,06	25	WK-10X180	81460010180
M10	10	200	45	0,08	20	WK-10X200	81460010200
M12	12	200	73	0,12	5	WK-12K200	81460012200

WKRETY DWUGWINTOWE (WK)

