

# CMP PRODUCTS

## CABLE CLEATS - REFERENCE GUIDE

- All products meet IEC 61914 to ensure safety of personnel and protection of equipment.
- LSF, Halogen-Free, UV, weather & corrosion resistant for longevity.
- Short circuit testing as standard to ensure the securing and retention of cables without damage.

CLEAT NAME & SPECIFICATION																			
	SABRE	VALIANT	FALCON	ZENITH	SOLACE	THEMIS	HELIOS	CYCLONE I	CYCLONE II	CYCLONE III	CYCLONE STRAP	TREFOIL RESTRAINT	PATRIOT	SOVEREIGN	CONQUEROR	HURON	RELIANCE	SAPPHIRE	
CLEAT TYPE	1 Bolt	1 Bolt	2 Bolt	2 Bolt	1 Bolt (High Temperature)	2 Bolt (High Temperature)	1 Bolt (High Temperature)	Double Strap	Double Strap	Triple Strap	2 or 3 Strap	Standard Duty Intermediate Restraint	Standard Duty Hinged	Heavy Duty Hinged	Range Taking Hinged	Light Duty Hinged	Standard Duty Hinged	Heavy Duty Hinged	
CABLE RANGE	10-57 mm	10-71 mm	38-135 mm	38-151 mm	10-71 mm	38-97 mm	10-65 mm	Single 36-165 mm Trefoil 24-145 mm Quad 21-124 mm	Single 36-165 mm Trefoil 24-145 mm Quad 21-124 mm	Single 36-165 mm Trefoil 24-145 mm Quad 21-124 mm	Single 36-165mm Trefoil 24-145 mm Quad 21-124 mm	19-130 mm	17-128 mm	17-128 mm	19-130 mm	19-128 mm	19-128 mm	19-150 mm	
CABLE FORMATION	○	○	○	○	○	○	○	○ ○ ○ ○	○ ○ ○ ○	○ ○ ○ ○	○ ○ ○ ○	○ ○ ○	○ ○ ○	○ ○ ○	○ ○ ○	○ ○ ○	○ ○ ○	○ ○ ○	○
NO OF SIZES	10	12	8	9	12	5	11	10 / 15 / 15	10 / 15 / 15	10 / 15 / 15	10 / 15 / 15	28	24	24	16	23	24	13	
FIXINGS	One Bolt Fixing	One Bolt Fixing	Two Bolt Fixing	Two Bolt fixing	One Bolt Fixing	Two Bolt Fixing	One Bolt Fixing	One or Two Bolt Fixing	One or Two Bolt Fixing	One or Two Bolt Fixing	NA	NA	One or Two Fixings	One or Two Fixings	One or Two Fixings	One or Two Fixings	One or Two Fixings	One or Two Fixings	
MATERIAL	Nylon, LSF or LUL approved polymer	Cast Aluminium	Nylon, LSF or LUL approved polymer	Cast Aluminium	Cast Stainless Steel 316L	Cast Stainless Steel 316L	Stainless Steel 316L	Aluminium Base Stainless Steel Strap	Stainless Steel Base Stainless Steel Strap	Stainless Steel Base Stainless Steel Strap	Stainless Steel 316L	Stainless Steel 316L	Stainless Steel 316L	Stainless Steel 316L	Stainless Steel 316L	Aluminium	Aluminium	Stainless Steel 316L	

CLEAT ORDERING CODES						
CLEAT NAME	CLEAT TYPE	SIZE RANGE	MATERIAL SUFFIX	MATERIAL	EXAMPLE CODES	
SABRE / VALIANT / SOLACE	1BC	1 Bolt Cleat	3238	Required range 32-38 mm	- Z LUL A HT The material only applies to the 1BC and 2BC range. Leave blank for nylon, Z for LSF, LUL for LUL approved polymer, A for aluminium and HT for high temperature stainless steel.	1BC3238HT
HELIOS	FPC	Fire Performance Cleat	2327	Required range 23-27 mm	-	FPC2327
ZENITH / FALCON / THEMIS	2BC	2 Bolt Cleat	048058	Required range 48-58 mm	- Z LUL A HT The material only applies to the 1BC and 2BC range. Leave blank for nylon, Z for LSF, LUL for LUL approved polymer, A for aluminium and HT for high temperature stainless steel.	2BC048058LUL
PATRIOT	SDSS	Standard Duty Stainless Steel	036042	Required range 36-42 mm	-	SDSS036042
SAPPHIRE	SHDSS	Single Heavy Duty Stainless Steel	050070	Required range 50-70 mm	-	SHDSS050070
HURON	LDAL	Light Duty Aluminium	019023	Required range 19-23 mm	-	LDAL019023
RELIANCE	SDAL	Heavy Duty Aluminium	023028	Required range 23-28 mm	-	SDAL023028
SOVEREIGN	HDSS	Heavy Duty Stainless Steel	082088	Required range 82-88 mm	-	HDSS082088
CONQUEROR	RTSS	Range Taking Stainless Steel	058067	Required range 58-67 mm	-	RTSS058067
CYCLONE I	1CYC	Light Duty 2 Loop Stainless Steel Strap	030041	Required range 30-41 mm	-	1CYC030041
CYCLONE II	2CYC	Standard Duty 2 Loop Stainless Steel Strap	030041	Required range 30-41 mm	-	2CYC030041
CYCLONE III	3CYC	Heavy Duty 3 Loop Stainless Steel Strap	030041	Required range 30-41 mm	-	3CYC030041
CYCLONE II STRAP	2STR	Standard Duty 2 Loop Intermediate Restraint	082095	Required range 82-095 mm	-	2STR082095
CYCLONE III STRAP	3STR	Heavy Duty 3 Loop Intermediate Restraint	132145	Required range 132-145 mm	-	3STR132145
TREFOIL INTERMEDIATE RESTRAINT	SDSSIR	Standard Duty Stainless Steel Intermediate Restraint	058062	Required range 58-62 mm	-	SDSSIR058062

### CLEAT RANGE

