Pipe Cutter

220

for steel pipes

- > Heavy duty pipe cutters.
- > Frame in malleable cast steel.
- > TUBEX®





	. 50	
4		
÷	Ϋ́	
	* **	

_	Code	No.	<u>⊘ mm</u>	Wall thickness	l⊲ mm ⊳l	→ kg →
	4503400	220020 1/8-2"	10-60	2.0-6.3	380	2.90
	Code	No.				
	220220	Spare Wheel				

Tin Snips

8516

scissors pattern

- > American Pattern.
- > Carbon steel SAE1045.
- > Drop forged and heat treated.
- > Cutting surfaces induction hardened.
- > Precision ground cutters.
- > Blue epoxy powder coated.

8531

straight pattern

- > English Pattern.
- > Carbon steel SAE1045.
- > Drop forged and heat treated.
- > Cutting surfaces induction hardened.
- > Precision ground cutters.
- > Blue epoxy powder coated.



Code	No.	l∢ mm ►l	$\Delta_{kg}\Delta$
675504	8516/250	250	0.525
675547	8516/300	300	0.675



Code	No.	∢ mm ⊳	∆ kg △
675784	8531/200 Left-hand Cutting	200	0.290
675792	8531/250 Left-hand Cutting	250	0.455
675806	8531/300 Left-hand Cutting	300	0.660

424

ideal pattern snips

- > For straight continuous and figure cuts.
- > With lever action.
- > Self-opening with installed spring and lock.
- > Polished cutting edges.
- > Sheet thickness maximum 1.2mm at strength of 600N/mm².

> Non-slip two-component handles.

425

figure snips

- > For straight continuous and figure cuts.
- > With lever action.
- > Self-opening with installed spring and lock.
- > Polished cutting edges.
- > Sheet thickness maximum 1.2mm at strength of 600N/mm².
- > Non-slip two-component handles.





Code	No.	∢ mm ⊳	$\Delta_{kg}^{\dagger}\Delta$	Code	No.	∢ mm ⊳	$\Delta_{kg}^{\dagger}\Delta$
4515410	424-260 Right-hand Cutting	160	530	4515760	425-260 Right-hand Cutting	260	480