

8040/1380X-01L13SA02-01L08SA01-01L15SA02 Art. No. 130908



- Flexible: Modular structure and 3 sizes enable customer-specific versions
- Lightweight enclosure made from glass fibre reinforced polyester resin (GRP), suitable for shipping industry and offshore

WebCode **8040B** 

With the R. STAHL Series 8040 control device system, you can get a clear overview of the control devices. The 3 combinable design sizes and the modular structure offer flexibility. You can choose from one standard version and customised variants.

Technical Data

Explosion Protection	
Scope of validity	IECEX European Union (ATEX)
Application range (zones)	1 2 21 22
IECEX gas certificate	IECEX PTB 06.0025
IECEX gas explosion protection	Ex db eb IIC T6 Gb
IECEX dust certificate	IECEX PTB 06.0025
IECEX dust explosion protection	Ex tb IIIC T80 °C Db
ATEX gas certificate	PTB 01 ATEX 1105
ATEX gas explosion protection	II 2 G Ex db eb IIC T6 Gb
ATEX dust certificate	PTB 01 ATEX 1105
ATEX dust explosion protection	II 2 D Ex tb IIIC T80 °C Db
Certificates	ATEX (PTB), Brazil (ULB), Canada (UL), China (NEPSI), IECEX (PTB), India (PESO), Korea (KGS), Taiwan (ITRI), USA (UL)
Ship approval	DNV GL
Electrical Data	
Rated operational voltage AC	550 V
Rated operational current	10 A (T6)


8040/1380X-01L13SA02-01L08SA01-01L15SA02 Art. No. 130908

Power dissipation	Vertical installation			
	Maximum surface temperature	Maximum permissible integrated power dissipation depending on the ambient temperature		
		-60 °C ≤ Ta ≤ +50 °C	-60 °C ≤ Ta ≤ +60 °C	-60 °C ≤ Ta ≤ +75 °C
	80 °C (T6)	1.1 W ¹⁾	0.8 W ²⁾	-
	95 °C (T5)	1.1 W ¹⁾	1.1 W ¹⁾	0.8 W ²⁾
	100 °C (T4)	1.1 W ¹⁾	1.1 W ¹⁾	0.8 W ²⁾
	¹⁾ 27 K - Max. temperature rise			
	²⁾ 20 K - Max. temperature rise			
	³⁾ 100 °C - Max. permissible service temperature (material limit)			
	Horizontal installation			
	Maximum surface temperature	Maximum permissible integrated power dissipation depending on the ambient temperature		
		-60 °C ≤ Ta ≤ +50 °C	-60 °C ≤ Ta ≤ +60 °C	-60 °C ≤ Ta ≤ +75 °C
	80 °C (T6)	1.1 W ¹⁾	-	-
	95 °C (T5)	1.1 W ¹⁾	1.1 W ¹⁾	-
	100 °C (T4)	1.1 W ¹⁾	1.1 W ¹⁾	0.8 W ²⁾
¹⁾ 30 K - Max. temperature rise				
²⁾ 23 K - Max. temperature rise				
³⁾ 100 °C - Max. permissible service temperature (material limit)				
Ambient Conditions				
Ambient temperature	-60 °C ... +60 °C (T6)			
Mechanical Data				
Degree of protection (IP)	IP66			
Degree of protection note	acc. to IEC/EN 60529			
Enclosure material	Polyester resin, Glass fibre reinforced			
Silicone-free	No			
AWG clamping range	AWG14			
Cover fixing type	With captive screws, M4 stainless steel screws			
Seal	Silicone, foamed			
Weight	0.68 kg			
Weight	1.5 lb			
Mounting / installation	Cable entry			
	Standard:	1 x M25 x 1.5; cable glands 8161; side below (D); directly mounted into enclosure wall		
	Special:	In side C (top) and/or D (bottom); 1 x M20 x 1.5; 1 x M25 x 1.5 Metal cable glands are possible; Mounting of metal cable glands in metal flange or via metal adapter plate		
	Flange			
	Standard:	without flange		
	Special:	with flange made of polyester resin or brass, can be mounted to sides C and D		

8040/1380X-01L13SA02-01L08SA01-01L15SA02 Art. No. 130908

Components	
Installation position top	Pushbutton Green - "I"
Built-in element top	Contact element NO
No. poles on top built-in el.	1
Installation position middle	Pushbutton Red - "0"
Built-in element middle	Contact element NC
No. poles on cen. built-in el.	1
Installation position bottom	Pushbutton Green - "II"
Built-in element bottom	Contact element NO
No. poles on bot. built-in el.	1
Flange and plates	Without flange, without plates
Cable glands and entries	1 x M25 Ø 7 to 17 mm
Entry type	Standard 8161, moulded material

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



ConSig 8040/13

Accessories

Pushbutton		Art. No.
BG001		
	Ø 39 mm Black Designation plate: Black, blank disc without text Silicone-free: No	223692

Spare Parts

Label holder		Art. No.
	Size 1, without insert disc, 1-line label for actuators Ø 39	223566
	Size 2, without insert disc, 1- or 2-line label for actuators Ø 39	223567

8040/1380X-01L13SA02-01L08SA01-01L15SA02 Art. No. 130908

	Size 3, without insert disc, 1-, 2- or 3-line label for actuators Ø 39	223568
Locking devices		Art. No.
	8602C3-753 for not actuated pushbutton BG001	244870
	8602C3-754 for actuated pushbutton BG001	244871
	8602C3-755 for not actuated pushbutton BG001	244872
Special key		Art. No.
	for tightening plastic locking nut	169101

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.