



## 8564 TWIN GRIP PULLERS



Code	No	Running Depth	Max. Opening	
<b>040010</b>	8564-2	100	110	1.0
<b>040030</b>	8564-3	140	150	1.9
<b>040050</b>	8564-4	200	200	2.3
<b>040440</b>	8564-4 HSPIL Puller & Spindle	105	200	3.7


## 8565 TRIPLE GRIP PULLERS



Code	No	Running Depth	Max. Opening	
<b>040020</b>	8565-2	80	120	1.3
<b>040040</b>	8565-3	140	160	2.5
<b>040060</b>	8565-4	200	220	4.0
<b>040450</b>	8564-4 HSPIL Puller & Spindle	105	220	4.6

## 8566 TWIN GRIP PULLERS




Code	No	Running Depth	Max. Opening	
<b>040070</b>	8566-1	300	300	9.8
<b>040080</b>	8566-2	400	400	10.8
<b>040495</b>	8566-1 HSP3 Puller & Spindle	105	300	10.1
<b>040500</b>	8566-2 HSP3 Puller & Spindle	110	370	11.1

## 8567 TRIPLE GRIP PULLERS

> Suitable for industrial purposes and heavy agricultural as well as construction machines.




Code	No	Running Depth	Max. Opening	
<b>040090</b>	8567-1	400	350	11.9
<b>040100</b>	8567-2	400	420	13.0
<b>040505</b>	8567-1 HSP3 Puller & Spindle	110	345	12.1
<b>040510</b>	8567-2 HSP3 Puller & Spindle	110	350	13.3

## 8568 TWIN GRIP PULLERS

> Heavy duty model for the removal of discs, pulleys, wheels, ball bearings etc.




Code	No	Running Depth	Max. Opening	
<b>040110</b>	8568-1	100	150	0.800
<b>040130</b>	8568-2	140	200	1.9

## 8569 TRIPLE GRIP PULLERS

> Heavy duty model for the removal of discs, pulleys, wheels, ball bearings etc.



Code	No	Running Depth	Max. Opening	
<b>040120</b>	8569-1	80	150	1.1
<b>040140</b>	8569-2	140	200	2.7