





Use:

761

> For use in all areas of assembly work where controlled tightening with low torque values is required (eg electronic hardware sector).

TORQUE WRENCH TSP SLIPPER

> For controlled nut and bolt tightening.

1-10Nm / pre-set

Features:

- > Pre-set production torque wrench without scale.
- > Square drive with ball-locking mechanism.
- > Integrated ratchet function for bi-directional tightening.
- > In accordance with DIN EN ISO 6789, traceable to national norms.

- > Actuation accuracy: +/-6% tolerance of the set torque.
- > Precision mechanism slides through very noticeably and audibly when the pre-set torque is achieved — over tightening is not possible.
- > Automatic resetting to the starting position.
- > Lightweight yet stable and corrosion resistant construction design.
- > ESD (electrostatic discharge) = electrostatically protected.
- > Black, non-slip rubber handgrip.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.

Code	No.	"		Nm	⊲ mm ►	$\Delta_{kg}^{+}\Delta$
1196650	761-05	1/4	6.3	1-5	185	0.190
1196731	761-10	1/4	6.3	2-10	185	0.190

762


TOROUE WRENCH TSC SLIPPER


1-10Nm

Use:

- > For use in all areas of assembly work where controlled tightening with low torque values is required (eg electronic hardware sector).
- > For controlled nut and bolt tightening.

- > Square drive with ball-locking mechanism.
- > Integrated ratchet function for bi-directional tightening.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Actuation accuracy: +/-6% tolerance of the set torque.





- > Lightweight yet stable and corrosion resistant construction design.
- **>** ESD (electrostatic discharge) = electrostatically protected.
- > Black, non-slip rubber handgrip.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



Code	No.	"		Nm	∢ mm ►	∆ kg ∆
1196480	762-05	1/4	6.3	1-5	195	0.235
1196510	761-10	1/4	6.3	2-10	195	0.235

TSC

TORQUE WRENCH ADJUSTABLE SLIPPER

10-90Nm







Use:

- > For use in all areas of assembly work where controlled tightening with low torque values is required (eg electronic hardware sector).
- > For controlled nut and bolt tightening.

- > Improved control of the fastening process by reducing the risk of both under and over tightening.
- > Unique slipping mechanism, which gives the operator more time to react once the target torque is
- > Actuation accuracy: +/- 6% tolerance of the set torque.

- > Maintains production output by minimising operator fatigue through the tool's ergonomic design.
- > Maximises productivity in restricted space through its compact slimline design.
- > EPA compliant for use in electrostatically sensitive applications.
- > Drive type made of stainless steel.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.
- > Accessories available.

Code	No.	"		Nm	i⊲ mm ⊳	∆ kg ∆
056060	TSC-45	1/4	6.3	10-45	195	0.235
056080	TSC-90	1/4	6.3	20-90	195	0.235