

## Double Ended Ring Spanners

### NO. 2 - OFFSET

- > Rings: thin walled with deep offset.
- > Chrome VANADIUM steel 31CrV3.
- > Carefully forged and professionally machined.
- > Ring: thin-walled, 5° deep offset from shaft, with UD profile for gentle transmission of force.

- > High bending strength does not fracture or splinter when overloaded, thus minimising the risk of injury.
- > In accordance with SANS 1112 and DIN 838.



## 2

### DOUBLE ENDED RING SPANNERS



Code	mm	mm	mm
601535	6x7	170	50
601551	8x9	182	65
601594	10x11	195	95
601659	12x13	212	120
601691	14x15	225	155
601721	16x17	245	210
601748	17x19	265	260
601756	18x19	265	260
601780	20x22	287	325
601799	19x24	305	410
601802	21x23	305	410
601837	24x26	325	475
601853	24x30	345	580
601861	25x28	345	580
601918	27x32	370	680
601926	30x32	370	680
601934	30x36	400	1000
601942	32x36	400	1100

Code	mm	mm	mm
003518	36x41	440	1150
003519	38x42	440	1200
003520	41x46	535	2250
003521	46x50	535	2150

### 2 AF RING SPANNER



Code	AF	mm	kg
003558	13/16x7.8"	285	0.360
003561	1.1/16x1.1/4"	370	0.700
003567	1.7/16x1.5/8"	440	1.300
003568	1.13/16x2"	540	2.200

## 2

### DOUBLE ENDED RING SPANNER SETS



- > Sets of the most used sizes.
- > Rings: thin walled with deep offset.
- > Chrome Vanadium steel 31CrV3.
- > In accordance with SANS 1112 and DIN 838.



Code	mm	Contents	kg
603058	2-8M	6x7 8x9 10x11 12x13 14x15 16x17 18x19 20x22	1.38
603112	2-11M	6x7 8x9 10x11 12x13 14x15 16x17 17x19 18x19 20x22 21x23 24x30	2.63
603090	2-12M	6x7 8x9 10x11 12x13 14x15 16x17 18x19 20x22 21x23 24x26 25x28 27x32	3.44