

## 20L (MM) SOCKETS 1/4"

hexagon, long pattern

- > Manually operated sockets with knurled base.
- > Chrome Vanadium steel 31CrV3.
- > Chrome plated and polished.
- > In accordance with SANS 1113 and DIN 3120.



| Code    | mm   | mm | kg    |
|---------|------|----|-------|
| 6191400 | 4.0  | 50 | 0.017 |
| 6191590 | 4.5  | 50 | 0.017 |
| 6191670 | 5.0  | 50 | 0.018 |
| 6191750 | 5.5  | 50 | 0.019 |
| 6191830 | 6.0  | 50 | 0.020 |
| 6191910 | 7.0  | 50 | 0.024 |
| 6192050 | 8.0  | 50 | 0.027 |
| 6192130 | 9.0  | 50 | 0.030 |
| 6192210 | 10.0 | 50 | 0.033 |
| 6192480 | 11.0 | 50 | 0.047 |
| 6192560 | 12.0 | 50 | 0.050 |
| 6192640 | 13.0 | 50 | 0.054 |



## ITX20 SCREWDRIVER BIT SOCKET 1/4"

for recessed TORX® head screws

- > Manually operated sockets with knurled base.
- > Chrome Vanadium steel 31CrV3.
- > Chrome plated and polished.
- > In accordance with SANS 1113 and DIN 3120.
- > TORX® = registered trademark of Acument Intellectual Properties, LLC. USA



| Code    | No.        |     | M         | mm   | mm   | kg    |
|---------|------------|-----|-----------|------|------|-------|
| 6190430 | ITX 20 T8  | T8  | M2,5      | 2,31 | 30.5 | 0.013 |
| 6190780 | ITX 20 T10 | T10 | M3 - M3,5 | 2,74 | 30.5 | 0.014 |
| 6190860 | ITX 20 T15 | T15 | M3,5 - M4 | 3,27 | 30.5 | 0.014 |
| 6190940 | ITX 20 T20 | T20 | M4 - M5   | 3,86 | 30.5 | 0.014 |
| 6191080 | ITX 20 T25 | T25 | M4,5 - M5 | 4,43 | 30.5 | 0.014 |
| 6191160 | ITX 20 T27 | T27 | M4,5 - M6 | 4,99 | 30.5 | 0.014 |
| 6191240 | ITX 20 T30 | T30 | M6 - M7   | 5,52 | 30.5 | 0.015 |
| 6265890 | ITX 20 T40 | T40 | M7 - M8   | 6,65 | 33.5 | 0.025 |

## IN20L (MM) SCREWDRIVER BIT SOCKET 1/4"

for in-hex screws, long pattern

- > Square drive as per DIN 3120 - C 6.3, ISO 1174, with ball retaining groove
- > Manually operated sockets with knurled base.
- > Chrome plated and polished.
- > Chrome Vanadium steel 31CrV3.



| Code    | mm | mm | kg    |
|---------|----|----|-------|
| 1933256 | 3  | 60 | 0.024 |
| 1933264 | 4  | 60 | 0.025 |
| 1933272 | 5  | 60 | 0.027 |
| 1933280 | 6  | 60 | 0.029 |
| 1933299 | 8  | 60 | 0.050 |



## IS 20 SCREWDRIVER BIT SOCKET 1/4"

for slotted head screws

- > Square drive as per DIN 3120 - C 6.3, ISO 1174, with ball retaining groove
- > Manually operated sockets with knurled base.
- > Chrome plated and polished.
- > Chrome Vanadium steel 31CrV3.



| Code    | No.           | mm  | mm  | mm | kg    |
|---------|---------------|-----|-----|----|-------|
| 6171560 | IS 20 4x0,8   | 4.0 | 0.8 | 28 | 0.011 |
| 6171640 | IS 20 5,5x1   | 5.5 | 1.0 | 28 | 0.012 |
| 6174230 | IS 20 6,5x1,2 | 6.5 | 1.2 | 28 | 0.012 |
| 6174310 | IS 20 8x1,6   | 8.0 | 1.6 | 28 | 0.012 |

## IKS 20 SCREWDRIVER BIT SOCKET 1/4"

for cross-head screws PH

- > Square drive as per DIN 3120 - C 6.3, ISO 1174, with ball retaining groove
- > Manually operated sockets with knurled base.
- > Chrome plated and polished.
- > Chrome Vanadium steel 31CrV3.



| Code    | No.      | PH | mm | kg    |
|---------|----------|----|----|-------|
| 6174580 | IKS 20 1 | 1  | 28 | 0.011 |
| 6174660 | IKS 20 2 | 2  | 28 | 0.012 |
| 6174740 | IKS 20 3 | 3  | 28 | 0.012 |



## IKS 20 PZD SCREWDRIVER BIT SOCKET 1/4"

for cross-head screws Pozi PZ

- > Square drive as per DIN 3120 - C 6.3, ISO 1174, with ball retaining groove
- > Manually operated sockets with knurled base.
- > Chrome plated and polished.
- > Chrome Vanadium steel 31CrV3.



| Code    | No.          | PZ | mm | kg    |
|---------|--------------|----|----|-------|
| 6187130 | IKS 20 PZD 1 | 1  | 28 | 0.012 |
| 6187210 | IKS 20 PZD 2 | 2  | 28 | 0.013 |
| 6187480 | IKS 20 PZD 3 | 3  | 28 | 0.014 |