

20L (MM) SOCKETS 1/4"

hexagon, long pattern

- > Manually operated sockets with knurled base.
- > Chrome Vanadium steel 31CrV3.
- > Chrome plated and polished.
- > In accordance with SANS 1113 and DIN 3120.



Code	⌀ mm	↳ mm	⚖ kg
6191400	4.0	50	0.017
6191590	4.5	50	0.017
6191670	5.0	50	0.018
6191750	5.5	50	0.019
6191830	6.0	50	0.020
6191910	7.0	50	0.024
6192050	8.0	50	0.027
6192130	9.0	50	0.030
6192210	10.0	50	0.033
6192480	11.0	50	0.047
6192560	12.0	50	0.050
6192640	13.0	50	0.054



ITX20 SCREWDRIVER BIT SOCKET 1/4"

for recessed TORX® head screws

- > Manually operated sockets with knurled base.
- > Chrome Vanadium steel 31CrV3.
- > Chrome plated and polished.
- > In accordance with SANS 1113 and DIN 3120.
- > TORX® = registered trademark of Acument Intellectual Properties, LLC. USA



Code	No.	⌀	▮ M	✦ mm	↳ mm	⚖ kg
6190430	ITX 20 T8	T8	M2,5	2,31	30.5	0.013
6190780	ITX 20 T10	T10	M3 - M3,5	2,74	30.5	0.014
6190860	ITX 20 T15	T15	M3,5 - M4	3,27	30.5	0.014
6190940	ITX 20 T20	T20	M4 - M5	3,86	30.5	0.014
6191080	ITX 20 T25	T25	M4,5 - M5	4,43	30.5	0.014
6191160	ITX 20 T27	T27	M4,5 - M6	4,99	30.5	0.014
6191240	ITX 20 T30	T30	M6 - M7	5,52	30.5	0.015
6265890	ITX 20 T40	T40	M7 - M8	6,65	33.5	0.025

IN20L (MM) SCREWDRIVER BIT SOCKET 1/4"

for in-hex screws, long pattern

- > Square drive as per DIN 3120 - C 6.3, ISO 1174, with ball retaining groove
- > Manually operated sockets with knurled base.
- > Chrome plated and polished.
- > Chrome Vanadium steel 31CrV3.



Code	⌀ mm	↳ mm	⚖ kg
1933256	3	60	0.024
1933264	4	60	0.025
1933272	5	60	0.027
1933280	6	60	0.029
1933299	8	60	0.050



IS 20 SCREWDRIVER BIT SOCKET 1/4"

for slotted head screws

- > Square drive as per DIN 3120 - C 6.3, ISO 1174, with ball retaining groove
- > Manually operated sockets with knurled base.
- > Chrome plated and polished.
- > Chrome Vanadium steel 31CrV3.



Code	No.	⌀ mm	mm	↳ mm	⚖ kg
6171560	IS 20 4x0,8	4.0	0.8	28	0.011
6171640	IS 20 5,5x1	5.5	1.0	28	0.012
6174230	IS 20 6,5x1,2	6.5	1.2	28	0.012
6174310	IS 20 8x1,6	8.0	1.6	28	0.012

IKS 20 SCREWDRIVER BIT SOCKET 1/4"

for cross-head screws PH

- > Square drive as per DIN 3120 - C 6.3, ISO 1174, with ball retaining groove
- > Manually operated sockets with knurled base.
- > Chrome plated and polished.
- > Chrome Vanadium steel 31CrV3.



Code	No.	⊕ PH	↳ mm	⚖ kg
6174580	IKS 20 1	1	28	0.011
6174660	IKS 20 2	2	28	0.012
6174740	IKS 20 3	3	28	0.012



IKS 20 PZD SCREWDRIVER BIT SOCKET 1/4"

for cross-head screws Pozi PZ

- > Square drive as per DIN 3120 - C 6.3, ISO 1174, with ball retaining groove
- > Manually operated sockets with knurled base.
- > Chrome plated and polished.
- > Chrome Vanadium steel 31CrV3.



Code	No.	⊕ PZ	↳ mm	⚖ kg
6187130	IKS 20 PZD 1	1	28	0.012
6187210	IKS 20 PZD 2	2	28	0.013
6187480	IKS 20 PZD 3	3	28	0.014