

## Slogging Spanners

### 306 (MM) / 306 (AF) RING SLOGGING SPANNERS

- > Chrome Vanadium steel 31CrV3.
- > Designed for heavy duty applications.
- > Shot blast finish.
- > In accordance with DIN 7444.



Code	mm	mm	kg
010001	24	185	0.30
010002	27	185	0.40
010003	30	195	0.50
010004	32	195	0.50
010035	34	195	0.40
010005	36	200	0.70
6474460	38	205	0.66
010006	41	225	0.80
010007	46	240	1.10
010008	50	250	1.20
6475940	55	260	1.50
6476080	60	270	1.60
6476160	65	290	2.20
6476240	70	325	2.50
6476320	75	325	3.20
6476400	80	345	3.60
6476590	85	345	3.90
6476670	90	380	7.00
6476750	95	380	7.00
6476830	100	410	6.60
6476910	105	415	9.60
6477050	110	435	9.60
6477130	115	435	9.60
6477210	120	480	9.80
6477480	125	510	9.80
6477560	130	510	13.60

### inch

Code	AF	mm	kg
010051	15/16"	185	0.40
010050	1"	185	0.40
010053	1.1/8"	185	0.40
010054	1.1/4"	195	0.50
010056	1.7/16"	200	0.70
010057	1.1/2"	200	0.60
010058	1.5/8"	225	0.80
010059	1.11/16"	225	0.80
010060	1.3/4"	240	1.10
010062	1.7/8"	240	1.10
010063	2"	250	1.20
6479930	2.3/16"	260	1.60
6480000	2.1/4"	260	1.60
6480190	2.3/8"	270	1.60
6480350	2.9/16"	290	2.20
6480430	2.5/8"	290	2.20
6480510	2.3/4"	325	2.40
6480780	3"	325	3.10
6480860	3.1/8"	345	3.70

### 133 (MM) OPEN ENDED SLOGGING SPANNERS

- > Chrome Vanadium steel 31CrV3.
- > Designed for heavy duty applications.
- > Shot blast finish.
- > In accordance with DIN 133.



Code	mm	mm	kg
009000	25	180	0.40
009002	27	180	0.40
009003	30	190	0.50
009004	32	195	0.60
009035	34	195	0.60
009005	36	210	0.80
009006	41	225	1.00
009007	46	255	1.30
009008	50	280	1.70
6400850	55	310	2.70
6400930	60	310	2.70
6401070	65	360	3.40
6401150	70	360	4.60
6401230	75	395	5.90
6401310	80	410	7.00
6401580	85	410	6.80
6401660	90	455	10.00
6401740	95	455	9.50
6401820	100	500	14.60
6401900	105	500	13.50
6402040	110	500	13.30
6402120	115	525	16.80
6402200	120	525	17.10

#### IMPACT SOCKETS

>56



#### 1" SOCKET SET

>53

