

VDE 2 E

VDE SINGLE ENDED RING SPANNERS

deep offset

- > Gedore Vanadium steel 31CrV3.
- > VDE insulation up to 1000 V, according to EN 60900/IEC 60900, two-ply Check-Tool insulation.



VDE 2 E 19



VDE 2 E 13

| Code | No. | ↳ mm ↳ | | |
|---------|-------------|--------|----|-------|
| 6036000 | VDE 2 E10mm | 170 | 10 | 0.097 |
| 6036190 | VDE 2 E11mm | 180 | 11 | 0.093 |
| 6036350 | VDE 2 E13mm | 190 | 13 | 0.130 |
| 6036430 | VDE 2 E14mm | 210 | 14 | 0.151 |
| 6036780 | VDE 2 E17mm | 220 | 17 | 0.199 |
| 6036860 | VDE 2 E19mm | 240 | 19 | 0.244 |
| 6037320 | VDE 2 E32mm | 330 | 32 | 0.683 |

VDE 894

VDE SINGLE OPEN ENDED SPANNERS

- > Gedore Vanadium steel 31CrV3.
- > VDE insulation up to 1000 V, according to EN 60900/IEC 60900, two-ply Check-Tool insulation.
- > Jaw set at 15°.



VDE 894 12



VDE 894 22

| Code | No. | ↳ mm ↳ | | |
|---------|--------------|--------|----|-------|
| 6572120 | VDE 894 10mm | 105 | 10 | 0.034 |
| 6572200 | VDE 894 11mm | 115 | 11 | 0.044 |
| 6572470 | VDE 894 13mm | 135 | 13 | 0.067 |
| 6572550 | VDE 894 14mm | 145 | 14 | 0.081 |
| 6572980 | VDE 894 17mm | 160 | 17 | 0.117 |
| 6573010 | VDE 894 19mm | 175 | 19 | 0.161 |
| 6574920 | VDE 894 32mm | 280 | 32 | 0.558 |

VDE 2133 NUT DRIVERS

with 3C handle



△ 1000 V

- > 3-component handles Power-Grip³ with hanging hole.
- > Ergonomic handle design.
- > Head depth 25mm, blade length 125mm.
- > VDE insulation up to 1000 V, according to EN 60900/IEC 60900.



| Code | No. | | ○ | Head Ø | |
|---------|-------------|-----|----|--------|-------|
| 1747045 | VDE 2133 3 | 225 | 3 | 9 | 0.109 |
| 1747053 | VDE 2133 4 | 225 | 4 | 10 | 0.111 |
| 1747061 | VDE 2133 5 | 225 | 5 | 11 | 0.112 |
| 1747088 | VDE 2133 6 | 225 | 6 | 12 | 0.114 |
| 1747096 | VDE 2133 7 | 235 | 7 | 14 | 0.152 |
| 1747118 | VDE 2133 8 | 235 | 8 | 15 | 0.154 |
| 1747126 | VDE 2133 9 | 235 | 9 | 16 | 0.154 |
| 1747134 | VDE 2133 10 | 245 | 10 | 17 | 0.161 |
| 1747142 | VDE 2133 11 | 245 | 11 | 19 | 0.193 |
| 1747150 | VDE 2133 12 | 245 | 12 | 20 | 0.196 |
| 1747169 | VDE 2133 13 | 245 | 13 | 21 | 0.199 |
| 1747177 | VDE 2133 14 | 245 | 14 | 22 | 0.198 |
| 1747185 | VDE 2133 17 | 245 | 17 | 26 | 0.222 |

VDE 2133 NUT DRIVER SET

10 pieces



△ 1000 V



| Code | No. | Contents | |
|---------|---------------|---|------|
| 1747260 | VDE 2133 / 10 | 2133 5,0 6,0 7,0 8,0 9,0 10,0 11,0 12,0 13,0 14,0 | 1.30 |

- > Only tools bearing these test symbols are classed as insulated tools.
- > VDE insulation as per standard EN60900, IEC/CEI900, VDE0680.
- > Safe working in high-voltage areas.
- > Up to 1000V alternating current.
- > Up to 1500V direct current.

