

## DREMOMETER

# 8554 TORQUE WRENCH DREMOMETER

6-30Nm / 50-270lbf·in

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 1/4" single square drive for controlled clockwise tightening.
- > 1/4" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Full-metal construction from high strength aluminium alloy.
- > Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



1/4"



±3%  
Accuracy



Code	Type	No.	■"	■	Contents	▬▬▬▬	Nm	lbf·in	◀mm▶	⚖
7775440		8554-01	1/4	6.3	in plastic box	1Nm / 10lbf·in	6-30	50-270	265	0.580

# 8560 TORQUE WRENCH DREMOMETER

8-40Nm / 70-350lbf·in

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 3/8" single square drive for controlled clockwise tightening.
- > 3/8" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Full-metal construction from high strength aluminium alloy.
- > Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



3/8"



±3%  
Accuracy



Code	Type	No.	■"	■	Contents	▬▬▬▬	Nm	lbf·in	◀mm▶	⚖
7682000		8560-01	3/8	10	in plastic box	5Nm / 50lbf·in	8-40	70-350	338	1.00

# 8561 TORQUE WRENCH DREMOMETER

20-120Nm / 15-90lbf·ft

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 1/2" single square drive for controlled clockwise tightening.
- > 1/2" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Full-metal construction from high strength aluminium alloy.
- > Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



1/2"



±3%  
Accuracy



Code	Type	No.	■"	■	Contents	▬▬▬▬	Nm	lbf·ft	◀mm▶	⚖
7683320		8561-01	1/2	12.5	in plastic box	5Nm / 5lbf·ft	20-120	15-90	462	1.50