

# 8562

## TORQUE WRENCH DREMOMETER

50-300Nm / 35-220lbf·ft

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 1/2" single square drive for controlled clockwise tightening.
- > 1/2" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Full-metal construction from high strength aluminium alloy.
- > Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



1/2"



Code	Type	No.	■"	■	Contents	▬▬▬▬▬	Nm	lbf-ft	◀mm▶	⚖
7685450		8562-01	1/2	12.5	in plastic box	5Nm / 5lbf-ft	50-300	35-220	617	2.0

# 8573

## TORQUE WRENCH DREMOMETER

40-200Nm / 30-150lbf·ft

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 1/2" single square drive for controlled clockwise tightening.
- > 1/2" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Full-metal construction from high strength aluminium alloy.
- > Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



1/2"



Code	Type	No.	■"	■	Contents	▬▬▬▬▬	Nm	lbf-ft	◀mm▶	⚖
7685530		8573-00	1/2	12.5	in plastic box	5Nm / 5lbf-ft	40-200	30-150	551	1.40

# 8563 D & DR

## TORQUE WRENCH DREMOMETER

140-760Nm / 105-560lbf·ft

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 3/4" single square drive for controlled clockwise tightening.
- > 3/4" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Full-metal construction from high strength aluminium alloy.
- > Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



3/4"



Code	Type	No.	■"	■	Contents	▬▬▬▬▬	Nm	lbf-ft	◀mm▶	⚖
7670180		8563-01 with extension tube	3/4	20	in plastic box	5Nm / 5lbf-ft	140-760	105-560	1400	5.00
7691500		8563-10	3/4	20	in plastic box		140-760	105-560	812	2.90