

# 8570

## TORQUE WRENCH DREMOMETER

80-360Nm / 60-260lbf·ft

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 3/4" single square drive for controlled clockwise tightening.
- > 3/4" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Full-metal construction from high strength aluminium alloy.
- > Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



Code	Type	No.	□"	■	Contents	▬▬▬▬	Nm	lbf-ft	↳ mm ◁	kg
7688470		8570-10	3/4	20	in plastic box	5Nm / 5lbf-ft	80-360	60-260	718	2.40

# 8571

## TORQUE WRENCH DREMOMETER

520-1000Nm / 380-730lbf·ft

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 3/4" single square drive for controlled clockwise tightening.
- > 3/4" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Full-metal construction from high strength aluminium alloy.
- > Double scale Nm and lbf.ft with scale graduation of 1Nm and 10lbf.in.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



Code	Type	No.	□"	■	Contents	▬▬▬▬	Nm	lbf-ft	↳ mm ◁	kg
7694010		8571-01	3/4	20	in plastic box with ALU extension tube	10Nm / 10lbf-ft	520-1000	380-730	800-1400	5.10

# 8564

## TORQUE WRENCH DREMOMETER

750-2000Nm

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 1" single square drive for controlled clockwise tightening.
- > 1" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Full-metal construction from high strength aluminium alloy.
- > Single scale Nm with scale graduation of 50Nm.
- > Extension tube with maximum lever length of 1998mm.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



Code	Type	No.	□"	■	Contents	▬▬▬▬	Nm		↳ mm ◁	kg
7695250		8564-01	1	25	with 2 extension tubes	50Nm	750-2000		932-2353	11.60