

# 8572

## TORQUE WRENCH DREMOMETER

1500-3000Nm

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 1.1/2" single square drive for controlled clockwise tightening.
- > 1.1/2" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Full-metal construction from high strength aluminium alloy.
- > Double scale with scale graduation of 50Nm.
- > Extension tube with maximum lever length of 2343mm.
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



Code	Type	No.	■"	■	Contents		Nm	lbf-in	l-mm	
7717160		8572-01	1.1/2	40	with 2 extension tubes	50Nm	1500-3000		1423-2343	13.20

# 753

## TORQUE WRENCH DREMOMETER MINI

2-12Nm

**Use:**

- > For use in almost all industrial manufacturing areas.
- > For controlled nut and bolt tightening.

**Features:**

- > Adjustable torque wrench with a 1/4" single square drive for controlled clockwise tightening.
- > 1/4" square drive with ball-locking mechanism as per DIN 3120.
- > In accordance with DIN EN ISO 6789, traceable to national norms.
- > Automatic short path actuation with tactile impulse and audible signal.
- > Actuation accuracy: +/- 3% tolerance of the scale set to torque.
- > Window with a magnifying-glass effect.
- > Double scale with a scale graduation of 0.5Nm and 5 lbf-in.
- > Additional micrometer scale for setting interim values with Nm, graduations of 0.05Nm
- > Supplied with a calibration certificate.
- > Unique serial number for traceability.



Code	Type	No.	■"	■	Contents		Nm	lbf-in	l-mm	
1957694	Mini	753-11	1/4	6.3	in plastic box	0,5Nm / lbf-in + 0,05Nm	2-12	18-106	211	0.320

# 8200

## TORQUE ANGLE INDICATOR

**Use:**

- > Additional angle regulated tightening for controlled torque and angle activation.

**Features:**

- > For additional precise angle tightening (0 - 360°)
- > 1/2" square drive with ball-locking device.
- > With sliding magnetic and gripping arm.
- > For use with a suitable torque wrench.
- > The maximum output of the torque wrench must not be exceeded.



Code	No.	■"	□"	∅ mm		
1195980	8200-01	1/2	1/2	80	0-360	0.330