

DVV-540RS

TORQUE MULTIPLIER DREMOPLUS ALU

54000Nm / 40330lbf·ft

2 1/2" ± 3%



Particularly suitable for:


- > Heavy industry.
- > Oil industry.
- > Petrochemicals.

Features:

- > Mechanical hand torque multiplier for controlled screw tightening and unloosening screw connections.
- > With a three-stage planet gear.
- > High-performance aluminium housing.
- > Chrome Vanadium steel reaction arm.
- > Multiplication at the ratio of 1:175.
- > With anti-wind-up ratchet (RS).
- > With non-destructive Slipper overload safety mechanism for gear protection - clockwise and anti-clockwise.
- > With fixture for welding on a reaction arm (optional).
- > Guaranteed accuracy: Better than +/- 3% tolerance.
- > For operation in combination with a torque wrench.
- > 1 model for a maximum load of around a maximum 54000Nm.
- > Output square drive with a drill hole - for sockets or impact sockets with a safety pin and ring.

Scope of delivery:

- > Torque Multiplier DREMOPLUS ALU.
- > Delivery in a sturdy crate on pallet.
- > Setting table.
- > Detailed technical information is available on request.



Code	No.	max. Nm Output	max. lbf-ft Output	Ratio	" C	" D	A	B	max. Nm Input	max. lbf-ft Input	Weight
2653168	DVV-540RS	54000	40330	1:175	3/4	2.1/2	270	415	380	280	64.5



SPECIAL REACTION ARMS CAN BE OBTAINED ON REQUEST INCLUDING TECHNICAL ADVICE.

- > Just turn to us - We would be glad to tender any advice.
- > Any problems you have represent our assignments!