

Technical Data Sheet



Smart® Tie 20mm (3/4") Manual Fitting Tool Part No. SM-FT-1000-20ST





Description


Pneumatic Fitting tool to tighten the Smart® Tie 20mm (3/4") strapping product. Also manually cuts the excess tail once tension has been achieved. Tool suitable for onshore and offshore use. Can be used subsea.



Outline Dimensions (General Tolerance ± 5mm)







General Properties							
Property	Value	Unit					
Weight ¹	2.60 (5.72) ± 2%	kg (lb)					
Length (A)	385 (15.2)	mm (inch)					
Width (B)	69 (2.7)	mm (inch)					
Height (C)	130 (5.1)	mm (inch)					

 $^{^{\}rm 1}\,{\rm Does}$ not include torque wrench supplied with tool

HCL Fasteners Ltd,

Registered Office, Clamping House, First Avenue, Westfield Industrial Estate, Radstock, BA3 4BS, VAT no 639389486 Registered No 2860032

Tel: +44 (0)1761 417714 Email: sales@hclfasteners.com Web: www.hclfasteners.com



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001=



Technical Data Sheet



Mechanical



Torque Settings and Tension										
Smart® Tie Material	Max Input Torque ²		Max System Force ³ (During Tightening)			Min Retention Force ³ (After Tightening)				
	Nm	lb-ft	N	kgf	lbf	N	kgf	lbf		
PA66 (Nylon 66)	8	5.9	3300	337	742	2000	204	450		
PA11 (Nylon 11)	7	5.2	2800	286	629	1400	143	315		
PA12 (Nylon 12)	7	5.2	2800	286	629	1400	143	315		
PPS (Polyphenylene	5	3.7	2400	245	540	1000	102	225		
Sulphide)				6.1						

²The input torque may need to be reduced depending on the aggressive nature of the application.

³ The final retention force has been measured on a 200mm diameter steel pipe. This figure may be lower for smaller diameters, or higher for larger diameters.



Further Operating Details, including tool setup, maintenance and parts list can be found in the following booklet:

SM-FT-1000 Banding Tool (Operation, Parts & Safety Manual | Original Instructions)



Important Notice to User

Storage: In offshore or corrosive environments tool should be washed with clean water, air dried and lightly sprayed with a corrosion inhibitor such as oil. Store in a cool dry area in original carton.

Warranty: HCL warrants that all products when stored, used and maintained in accordance with HCL's written instructions will meet or exceed the above specification. HCL makes no other warranties or conditions, expressed or implied, including, but not limited to, any implied warranty or condition of merchantability or fitness for a particular purpose or any implied warranty or condition arising out of a course of dealing, custom or usage of trade. If any HCL product does not conform to this warranty then only replacement or refund of the affected parts will be considered.

Limitation of Liability: Except where expressly prohibited by law, HCL will not be liable for any damage or loss arising from the use of the HCL product.

Product Use: It is the user's responsibility to determine the suitability of the product for the task it is to be used for. HCL reserve the right to continually improve its product and would advise the user to contact HCL at all times to ensure they have up to date current data to work with.

HCL Fasteners Ltd, Registered Office, Clamping House, First Avenue, Westfield Industrial Estate, Radstock, BA3 4BS, VAT no 639389486 Registered No 2860032 Tel: +44 (0)1761 417714

Email: sales@hclfasteners.com
Web: www.hclfasteners.com

