




nVent CADDY Speed Link SLS with Wedge Anchor – SLS2L3WA6 (196759)



- Complete system includes wire, locking device and wedge anchor from Powers Fasteners, Inc.
- Quickly and easily attaches into cracked and non-cracked concrete
- Installs in strut profiles without the need to insert fingers or tools into the strut
- Finger tightening of nut secures the locking device into position without tools
- No special tools required
- ETA-13/0106 assessment available for wedge anchor from Powers Fasteners, Inc



Part Number	SLS2L3WA6
Article Number	196759
Material	Steel Polypropylene Zinc Alloy
Finish	Electrogalvanized
Static Load Safety Factor	5:1
Complies With	SMACNA HVAC-DCS
Wire Rope Diameter	2 mm
Wire Rope Length	3 m
Length (L)	63.5 mm
Drill Bit Diameter	6 mm
Drill Hole Depth	60 mm
Embedment Depth	55 mm Min
Static Load (F)	270 N
Thread Size (TS)	M8
Height 1 (H1)	53 mm
Height 2 (H2)	43.5 mm
Width (W)	16 mm
Thickness (T)	4 mm Max

Part Number	SLS2L3WA6
Hole Size (HS)	8 – 10 mm
Slot Size (SS)	8 x 6.5 mm - 8 x 10 mm
Certifications	cULus
Standard Packaging Quantity	10 pc
UPC	78285692746
EAN-13	0782856927464

The 2 mm locking device is compatible with C-Channel Types E0 and E0L.

Total load per wire on a multi-tier trapeze must not exceed static load.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

