



Combining advanced ergonomics, permanent comfort and peak performance, AGERA[™] incorporates durable nylon and lightweight TPE to offer stylish protection for permanent wear.

SPECIAL FEATURES





VERSIONS		REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	\bigcirc	RLY00011	2C-1.2 € 1FKN C€	€ EN 166 F € €	Impacts, UV radiations	
GREY	\bigcirc	RLY00012	5-2.5 € 1FKN C€	€ EN 166 F € €	Impacts, UV and Solar radiations	TECTON 400 ⁻ K&N Anti-scratch and Anti-fog / UV400 / moisture repellent
BLUE	\bigcirc	RLY00014	2-1.4 € 1FKN C€	€ EN 166 F € €	Impacts, UV radiations	
INDOOR/OUTDOOR	\bigcirc	RLY00013	2-1.4 🕑 1F 🤇 E	€ EN 166 F € €	Impacts, UV radiations	S ARIDA Moisture Repellent + Anti-fog

See overleaf for this product's technical specification>

AGERA[™]

GENERAL SPECIFICATION

Individually contained in a polythene bag

9mm

29g

10

200

LENS BASE

PACKAGING

with a Euroslot

PER CARTON

WEIGHT

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES	
LENS	Polycarbonate	One piece, moulded	
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Ventilated	
TEMPLE	TR90 Thermoplastic/ Thermoplastic Elastomers (TPE)	Co-injected - Durable, flexible and lightweight	
HINGE	TR90 Thermoplastic/ Metal	Increased strength	

FRAME MARKINGS

C Identity of the manufacturer

MECHANICAL STRENGTH:

CE Certification mark

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto

F Low energy impact, resists a 6mm, 0.86 g ball at 45 m/s

the ground, ageing by light exposure, exposure to heat or corrosion etc.

Ríley *C*

LENS MARKINGS

LENS FILTER TYPE: 2, 2C UV 5 Solar

SCALE NUMBER (SHADE):

- **1.2** Clear or Amber**1.4** Blue or I/O Waterproof
- 2.5 Grey

 ${\mathscr C}$ Identity of the manufacturer

- OPTICAL CLASS:
- 1 High optical quality
- MECHANICAL STRENGTH:
- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s

PERFORMANCE:

- ${\bf K}$ $\;$ Resistance to scratches by fine particles $\;$
- N Resistance to fogging
- CE Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

 MAINTENANCE:
 Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

 STORAGE:
 All products must be stored in a dry and clean environment.

PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

www.riley-eyewear.com

E: info@riley-eyewear.com T: +44 (0)161 877 4747 F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

EC-Type certification issued by: 0530: CERTOTTICA SCARL, Zona Industriale Villanova, 32013 - Longarone (BL), Italy 0194: INSPEC, 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, United Kingdom The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.



© 2017 Globus (Shetland) Ltd | RILEY-DATA-AGERA-0417