



# A12 Standard Coupler, Plain, Worldwide Design – EL18A12N



- Designed to splice the same diameter bars where the second bar can be rotated and is not restricted in its axial direction
- Slim design maintains concrete cover
- Installs quickly and easily



Part Number	EL18A12N
Material	Steel
Finish	Plain
Design Version	Worldwide (Globally Available Materials)
Rebar Size, Metric	18 mm
Hex Width (W)	27 mm
Length (L)	72 mm
Bar Depth (BD)	29 mm
Bar Gap (BG)	14 mm
Unit Weight	0.25 kg
Designed to Meet	AASHTO ABNT NBR 8548:1984 ACI 318 Type 1 (125% Specified Yield) ACI 318 Type 2 (Specified Tensile) ACI 349 ACI 359 AS3600 BS EN 1992-1-1 BS EN 1992-2 CAN/CSA - N287.2/.3/.4 DIN EN 1992-1-1 Eurocode 2 IBC Type 1 (125% Specified Yield) IBC Type 2 (Specified Tensile) ISO 15835 NEN EN 1992-1-1 NF A 35-020-1 NF EN 1992-1-1 ÖNORM EN 1992-1-1 Sellafeld Ltd. Std. ES_0_3110 US Army Corps of Engineers
Certifications	EMI 20-CPR-244 (Hungary) FCC US B1447 NP01 0048 (Russian Federation) IAPMO®-UES ER-0129 (United States) INCERC AT 001ST-01-140-2014 (Romania) ITB LA City Approval ER-0129 (United States)

Part Number	EL18A12N
	MOCT RU MCC 157 313 33439 [Russian Federation] TZUS 204-C5-2016-070-049998 [Czech Republic]
Standard Packaging Quantity	70 pc
UPC	78285669475
EAN-13	8711893047783

Bar dimensions and weights listed may vary by region. Coupler sizes not shown may be available by special order. Contact your nVent LENTON representative for more information.

IAPMO is a registered trademark of International Association of Plumbing and Mechanical Officials.

**WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved  
nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.  
All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.