



TYPE P100A



TYPE P100C

Mounting Brackets

Mounting brackets are used to mount regulators securely to the container or to the side of the building.

| Mounting Brackets | | |
|----------------------------|---------------|--------|
| REGULATOR TYPE | BRACKET STYLE | |
| | Triangular | Bowtie |
| R622, R632, R642 and R622H | P100A | P100C |
| R122H, R222 and R232 | P100A | ---- |
| 912 | P100A | ---- |



TYPE 50-2



TYPE 50P-5



TYPE 50P-2

Test Gauge Assemblies

The 50 Series test gauges are used to check appliance line pressure after the regulator has been installed.

| Test Gauge Assemblies | | | | |
|-----------------------|------------------|------|---------|------------------------|
| TYPE | INLET CONNECTION | HOSE | PLASTIC | RANGE, IN. W.C. / mbar |
| 50-2 | 1/4 in. MNPT | No | No | 0 to 35 / 0 to 87 |
| 50P-2 | Female Hose | Yes | Yes | |
| 50P-5 | | Yes | No | |



TYPE P499



TYPE P500

Adaptor With Screen (Type P499)

Used to convert a 1/4 in. NPT inlet on regulators such as Types 912 and 67C to an inverted flare.

Type P500 Plug

Keeps dirt and foreign material from entering changeover assemblies. 1/4 in. Inverted Flare.

Type P501 Filter Assembly

Intended for the inlet of 67C Series regulators, the Type P501 prevents foreign material from reaching the regulator's valve disc.

| Adaptor with Screen | |
|---------------------|---------------------------------------|
| TYPE | SIZE |
| P499 | 1/4 in. Inverted Flare x 1/4 in. MNPT |



TYPE J542
BOTTOM CONNECTION



BACK CONNECTION

Pressure Gauges

Fisher™ offers pressure gauges with bottom or back connection for LPG service. The back connection makes a more compact assembly on installations where space is limited. All gauges have a 2 in. / 51 mm diameter face/black Terluran® plastic case.

| Pressure Gauges | | | | | | | |
|----------------------------------|-----------|--------------------|--------------------|--------------------|--------------------|----------------------|----------------------|
| PRESSURE GAUGE RANGE, psig / bar | | | | | | | |
| Connection | Size, in. | 0 to 15 / 0 to 1.0 | 0 to 30 / 0 to 2.1 | 0 to 60 / 0 to 4.1 | 0 to 160 / 0 to 11 | 0 to 300 / 0 to 20.7 | 0 to 400 / 0 to 27.6 |
| Bottom | 1/4 | J500 | J501 | J502 | J504 | J506 | J542 ⁽¹⁾ |
| Back | 1/4 | J510 | J511 | J512 | J514 | J516 | N/A |

1. For LPG or Anhydrous ammonia (NH₃) service.

Terluran® is a trademark of BASF.