



Standard Universal Sway Brace – CSBSTU0250EG (404389)



- Use for both lateral and longitudinal sway brace applications
- Snap-off bolt head helps enable easy installation and inspection of seismic sway braces
- Works with 1" through 2" brace pipes and 1/4" angle iron braces to reduce inventory
- Slotted design grabs service pipe for added gripping strength
- Meets NFPA®-13 requirements for seismic sway bracing
- Meets CEN/TS 17551:2021 requirements for Seismic Sway Bracing



Part Number	CSBSTU0250EG
Article Number	404389
Material	Steel Cast Iron
Finish	Electrogalvanized
Pipe Size	2 1/2"
NB/DN	65
A	225.4 mm
B	30.2 mm
Brace Pipe Size	1" – 2"
Brace NB/DN	25 – 50 mm
Certifications	cULus FM Approved, Seismic OSH PD
Standard Packaging Quantity	10 pc
UPC	78285663453
EAN-13	8711893128154

UL Loads			
Part Number	Lateral	Longitudinal	Brace Member
	EN 10250 H EN 10255 M	EN 10250 H EN 10255 M	
CSBSTU0100EG	5340 N	N/A	25 mm - 50 mm EN10255H
CSBSTU0125EG	5340 N	N/A	25 mm - 50 mm EN10255H
CSBSTU0150EG	5340 N	N/A	25 mm - 50 mm EN10255H
CSBSTU0200EG	5340 N	N/A	25 mm - 50 mm EN10255H
CSBSTU0250EG	9100 N	6115 N	25 mm - 50 mm EN10255H
CSBSTU0300EG	7115 N	3110 N	25 mm - 50 mm EN10255H
CSBSTU0400EG	9100 N	6115 N	25 mm - 50 mm EN10255H
CSBSTU0500EG	9100 N	6115 N	25 mm - 50 mm EN10255H
CSBSTU0600EG	9100 N	4890 N	25 mm - 50 mm EN10255H
CSBSTU0800EG	9100 N	6115 N	25 mm - 50 mm EN10255H
CSBSTU0250EG	9100 N	8385 N	25 mm - 50 mm EN10255H

FM Loads (EN 10255 L, EN10255 M and EN 10255 H Service Pipes)								
Part Number	Horizontal Capacity per Installation Angle from Vertical							
	Lateral				Longitudinal			
	30° - 44°	45° - 59°	60° - 74°	75° - 90°	30° - 44°	45° - 59°	60° - 74°	75° - 90°
CSBSTU0100xx	3825 N	5425 N	6670 N	7430 N	4315 N	3200 N	3825 N	4270 N
CSBSTU0125xx	3825 N	5425 N	6670 N	7430 N	4315 N	3200 N	3825 N	4270 N
CSBSTU0150xx	3825 N	5425 N	6670 N	7430 N	4315 N	3200 N	3825 N	4270 N
CSBSTU0200xx	6805 N	9610 N	11790 N	13165 N	3870 N	3070 N	3690 N	4136 N
CSBSTU0250xx	6805 N	9610 N	11790 N	13165 N	3870 N	3070 N	3690 N	4136 N
CSBSTU0300xx	6805 N	9610 N	11790 N	13165 N	3870 N	3070 N	3690 N	4136 N
CSBSTU0400xx	6985 N	9875 N	12100 N	13480 N	6895 N	6185 N	7475 N	8320 N
CSBSTU0500xx	6985 N	9875 N	12100 N	13480 N	6895 N	6185 N	7475 N	8320 N
CSBSTU0600xx	8805 N	12500 N	15300 N	17080 N	6540 N	5205 N	6270 N	6985 N

FM Loads (4.8 mm wall and EN 10255 H Service Pipes)								
Part Number	Horizontal Capacity per Installation Angle from Vertical							
	Lateral				Longitudinal			
	30° - 44°	45° - 59°	60° - 74°	75° - 90°	30° - 44°	45° - 59°	60° - 74°	75° - 90°
CSBSTU0800xx	9075 N	12855 N	15745 N	17570 N	5340 N	7560 N	9295 N	10365 N
CSBSTU1000xx	9075 N	12855 N	15745 N	17570 N	5340 N	7560 N	9295 N	10365 N

FM is a registered certification mark of FM Approvals LLC, LTD. NFPA is a registered trademark of National Fire Protection Association, Inc. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

