SOSR Stand Off Two Hole Strap for CPVC Pipe – SOSR150 (597808)













- Includes flared edges to protect piping
- Rated for use with CPVC fire sprinkler pipe
- Positions pipe 1-1/2" (38 mm) off the mounting surface eliminating the need for wooden spacer blocks
- Can be mounted in both vertical and horizontal positions on concrete, steel and wood
- Meets the UL® 203 stringent upward thrust requirement
- UL® Listed as both a hanger and pipe restrainer
- Complies with static load requirements of NFPA® 13
- Includes mounting screws
- Can be used with 3TW backing nut on composite wood joist installations







Part Number	SOSR150
Article Number	597808
Material	Steel
Finish	Pregalvanized
Pipe Size	1 1/2"
NB/DN	40
Hole Size (HS)	5.1 mm
A	98 mm
В	114 mm
С	25.4 mm
Thickness (T)	1.61 mm
Hanger Spacing	2.1 m Max
Certifications	cULus
Standard Packaging Quantity	100 рс
UPC	78285666386
EAN-13	8711893100488



NFPA is a registered trademark of National Fire Protection Association, Inc. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

New tproducts shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

