



TYPE Y602-1 (UMBRELLA TYPE)



TYPE Y602-13 (ANGLE TYPE)

Vent Assemblies

Attached directly to the regulator vent connection to a regulator vent line, vent assemblies should be pointed downward on outdoor installations to avoid moisture build-up in the regulator spring case. Units with stabilizer assembly are intended for regulators with stability problems. The stabilizer gives a restricted breathing rate under normal conditions, opening for rapid discharge when necessary. Screen material is Monel® with integral plastic screen for all except Type Y602-12.

| Vent Assemblies | | | |
|-----------------|------------|---|------------|
| TYPE | | SIZE | STABILIZER |
| Umbrella Type | Angle Type | | |
| ---- | Y602-13 | 1/4 in. FNPT | No |
| ---- | Y602-14 | | Yes |
| Y602-1 | ---- | 1/4 in. MNPT | No |
| Y602-2 | ---- | | Yes |
| Y602-3 | ---- | 3/8 in. O.D. Tubing (Flare Connection) | No |
| Y602-4 | ---- | | Yes |
| Y602-12 | ---- | 1/4 in. MNPT | No |
| ---- | Y602-5 | 3/8 in. FNPT | No |
| ---- | Y602-6 | | Yes |
| ---- | Y602-7 | 1/2 in. FNPT | No |
| ---- | Y602-8 | | Yes |
| ---- | Y602-9 | 3/4 in. FNPT | No |
| ---- | Y602-23 | 3/4 in. MNPT | No |
| ---- | Y602-25 | 1 in. MNPT | No |



TYPE 912-101

Small Portable Appliance Regulators

Type 912 – Designed for use on small portable outdoor appliances.

Underwriters Laboratory (UL®) requires horizontally mounted regulators to be installed with vent opening protection to prevent blockage by freezing rain. The 912 Series has a temperature rating of -20 to 160°F / -29 to 71°C.

| Appliance Regulators | | | | | | | | | | | | | |
|-------------------------|-----------------|------------------|-----------------|------|------------------------------------|----------------|-----------------|------------------|-----|-------------------|-----|--------------|------|
| TYPE | PRESSURE RANGE | | OUTLET PRESSURE | | Capacities in BTU per hour Propane | | | INLET CONNECTION | | OUTLET CONNECTION | | ORIFICE SIZE | |
| | In. w.c. | mbar | In. w.c. | mbar | 10 psig, Inlet | 25 psig, Inlet | 100 psig, Inlet | In. | mm | In. | mm | In. | mm |
| 912N-194 ⁽¹⁾ | 3 to 7 | 7 to 17 | 5 | 12 | 101,000 | 151,000 | ---- | 1/4 | 6.4 | 1/4 | 6.4 | 0.073 | 1.85 |
| 912-104 | 9.25 to 13 | 23 to 32 | 11 | 27 | 101,000 | 270,000 | 349,000 | 1/4 | 6.4 | 1/4 | 6.4 | 0.073 | 1.85 |
| 912N-109 ⁽¹⁾ | 5 to 10 | 12 to 25 | 7 | 17 | 123,000 | 232,000 | 556,000 | 1/4 | 6.4 | 3/8 | 9.5 | 0.073 | 1.85 |
| 912-101 | 9.25 to 13 | 23 to 32 | 11 | 27 | 110,000 | 201,000 | 494,000 | 1/4 | 6.4 | 3/8 | 9.5 | 0.073 | 1.85 |
| 912-122 | 9.25 to 13 | 23 to 32 | 11 | 27 | 110,000 | 201,000 | 494,000 | 1/4 | 6.4 | 3/8 | 9.5 | 0.073 | 1.85 |
| 912H-108 | 0.5 to 2.7 psig | 0.03 to 0.19 bar | 1.5 psig | 103 | 131,000 | 202,000 | 470,000 | 1/4 | 6.4 | 3/8 | 9.5 | 0.094 | 2.39 |

1. Not UL listed.