



- **Anti-corrosion protection:** zinc-plated coating.
- **Connecting screws:** with head pozi drive Z2 (from PX-20-015 to PX-20-088) or with hexagonal head (from PX-20-108 to PX-20-168).

**PIPE CLAMPS FOR COLD SYSTEMS PX-20**

Clamps with PUR insert, insulation thickness 20 mm													
External pipe diameter D [mm] Cu [d]Fe [d]	Thickness insulation G [mm]	Length insulation B [mm]	Connection			Connecting screws M <sub>2</sub>	Clamp dimensions A x g [mm]L [mm]		Permissible load [kN]	Mass [kg]	Designation for the order	Part number	Download file DWG
			Version	Size High h [mm]	M <sub>1</sub>		A	g					
15	20	50	M8	5,3	A	M6	101	24x2,0	2,50	0,29	PX-20-015	0212001500	<a href="#">DWG</a>
18	17,2	20	M8	5,3	A	M6	101	24x2,0	2,50	0,30	PX-20-017	0212001700	<a href="#">DWG</a>
22	21,3	20	M8	5,3	A	M6	110	24x2,0	2,50	0,32	PX-20-021	0212002100	<a href="#">DWG</a>
28	26,9	20	M8	5,3	A	M6	115	24x2,0	2,50	0,36	PX-20-026	0212002600	<a href="#">DWG</a>
35	33,7	20	M10/M12	17,5	B	M6	130	26x2,5	2,50	0,46	PX-20-033	0212003300	<a href="#">DWG</a>
42	42,4	20	M10/M12	17,5	B	M6	136	26x2,5	2,50	0,50	PX-20-042	0212004200	<a href="#">DWG</a>
	48,3	20	M10/M12	17,5	B	M6	149	26x2,5	2,50	0,55	PX-20-048	0212004800	<a href="#">DWG</a>
54	54	20	M10/M12	17,5	B	M6	146	26x2,5	2,50	0,58	PX-20-054	0212005400	<a href="#">DWG</a>
57	57	20	M10/M12	17,5	B	M6	146	26x2,5	2,50	0,60	PX-20-057	0212005700	<a href="#">DWG</a>
	60,3	20	M10/M12	17,5	B	M6	155	26x2,5	2,50	0,62	PX-20-060	0212006000	<a href="#">DWG</a>
64	63,5	20	M10/M12	17,5	B	M6	155	26x2,5	2,50	0,64	PX-20-063	0212006300	<a href="#">DWG</a>
76,1	76,1	20	M10/M12	17,5	B	M6	170	26x2,5	2,50	0,72	PX-20-076	0212007600	<a href="#">DWG</a>
88,9	88,9	20	M10/M12	17,5	B	M6	183	26x2,5	2,50	0,82	PX-20-088	0212008800	<a href="#">DWG</a>
108	108	20	M10/M12	25,0	C	M8	220	35x3,0	3,90	1,18	PX-20-108	0212010800	<a href="#">DWG</a>
	114,3	20	M10/M12	25,0	C	M8	220	35x3,0	3,90	1,21	PX-20-114	0212011400	<a href="#">DWG</a>
133	133	20	M10/M12	25,0	C	M8	236	35x3,0	3,90	1,35	PX-20-133	0212013300	<a href="#">DWG</a>
	139,7	20	M10/M12	25,0	C	M8	236	35x3,0	3,90	1,38	PX-20-139	0212013900	<a href="#">DWG</a>
159	159	20	M10/M12	25,0	C	M8	284	35x3,0	3,90	1,60	PX-20-159	0212015900	<a href="#">DWG</a>
	168,3	20	M10/M12	25,0	C	M8	286	35x3,0	3,90	1,69	PX-20-168	0212016800	<a href="#">DWG</a>

