


KCS45 Tubular angle terminal

for multi-wire Cu cables



Material: galvanically tinned copper
Non tinned on request.

Cross section [mm ²]	For screw M	d ₂ [mm]	Symbol	s [mm]	d ₁ [mm]	d ₃ [mm]	a [mm]	l ₁ [mm]	l ₂ [mm]	Weight [g/pce]	Unit [pcs]	Dies discriminant	Crimping tools					
6	5	5,3	KCS45 5-6	1	4	9,5	9	8	8,5	3,90	10	6	EPZC300, EPZ300, GZ300, HRZ300, PRZ240, PR33, GO300, HR300, GU300, GU120, HR100-U, PR240, PR50, PP19, A11/6					
	6	6,4	KCS45 6-6											10	7,5	8,5	3,73	
10	5	5,3	KCS45 5-10	1,2	4,5	12	10	8	8,5	5,93	10	7		EPZC300, EPZ300, GZ300, HRZ300, PRZ240, GO300, HR300, GU300, GU120, HR100-U, PR240, PR50, R50, PP19				
	6	6,4	KCS45 6-10												12	7,5	8,5	6,14
	8	8,4	KCS45 8-10												13	10	11	6,60
16	6	6,4	KCS45 6-16	1,5	5,5	13	13	7,5	8,5	10,00	10	8		HR300, GU300, GU120, HR100-U, PR240, PR50, R50, PP19				
	8	8,4	KCS45 8-16												13	10	11	10,50
	10	10,5	KCS45 10-16												17	12	13	11,80
25	6	6,4	KCS45 6-25	1,5	7	14	15	7,5	8,5	14,00	10	10		PP19 + as below				
	8	8,4	KCS45 8-25												16	10	11	15,00
	10	10,5	KCS45 10-25										18		12	13	14,90	
	12	13	KCS45 12-25										18		13	14	18,10	
35	6	6,4	KCS45 6-35	1,75	8,5	17	17	7,5	8,5	22,30	10	12	EPZC300, EPZ300, GZ300, HRZ300, PRZ240, GO300, HR300, GU300, GU120, HR100-U, PR240, PR120, PR150, PR50, PP19, A11/6					
	8	8,4	KCS45 8-35											17	10	11	24,20	
	10	10,5	KCS45 10-35											19	12	13	25,20	
	12	13	KCS45 12-35											21	13	14	26,30	
	14	15	KCS45 14-35											21	15,5	15,5	27,70	
50	8	8,4	KCS45 8-50	2	10	20	19	10	11	33,20	10	14		HR100-U, PR240, PR120, PR150, PR50, PP19, A11/6				
	10	10,5	KCS45 10-50												20	12	13	34,60
	12	13	KCS45 12-50												23	13	14	33,30
	14	15	KCS45 14-50												23	15,5	15,5	39,10
	16	17	KCS45 16-50												28	16	17	43,20
70	8	8,4	KCS45 8-70	2,25	12	23,5	21	10	11	51,20	10	16	EPZC300, EPZ300, GZ300, HRZ300, PRZ240, GO300, HR300, GU300, GU120, HR100-U, PR240, PR120, PR150					
	10	10,5	KCS45 10-70											23,5	12	13	50,90	
	12	13	KCS45 12-70											23,5	13	14	55,10	
	14	15	KCS45 14-70											23,5	15,5	15,5	55,10	
	16	17	KCS45 16-70											28	16	17	61,40	
95	10	10,5	KCS45 10-95	2,25	13,5	26	25	12	13	58,612	1	18		EPZC300, EPZ300, GZ300, HRZ300, PRZ240, GO300, HR300, GU300, GU120, HR100-U, PR240, PR120, PR150				
	12	13	KCS45 12-95												26	13	14	59,11
	14	15	KCS45 14-95												26	15,5	15,5	67,90
	16	17	KCS45 16-95												28	16	17	69,00
	20	21	KCS45 20-95												34	19	20	74,00
120	10	10,5	KCS45 10-120	2,25	15,5	29	26	12	13	75,17	1	19	PR150					
	12	13	KCS45 12-120											29	13	14	76,40	
	14	15	KCS45 14-120											29	15,5	15,5	87,60	
	16	17	KCS45 16-120											30	16	17	88,90	
	20	21	KCS45 20-120											36	19	20	89,56	
150	10	10,5	KCS45 10-150	2,25	17	31	30	12	13	89,46	1	20	EPZC300, EPZ300, GZ300, HRZ300, PRZ240, GO300, HR300, GU300, PR240, PR150					
	12	13	KCS45 12-150											31	13	14	90,23	
	14	15	KCS45 14-150											31	15,5	15,5	93,50	
	16	17	KCS45 16-150											31	16	17	95,60	
	20	21	KCS45 20-150											36	19	20	97,70	
185	10	10,5	KCS45 10-185	2,5	19	35	30	12	13	115,00	1	23	PR240, PRZ240, + as below					
	12	13	KCS45 12-185											35	13	14	120,00	
	14	15	KCS45 14-185											35	15,5	15,5	120,30	
	16	17	KCS45 16-185											35	16	17	117,95	
	20	21	KCS45 20-185											39	19	20	123,23	
240	12	13	KCS45 12-240	2,5	21,5	39	35	13	14	140,00	1	25	EPZC300, EPZ300, GZ300, HRZ300, PRZ240, GO300, HR300, GU300					
	14	15	KCS45 14-240											39	15,5	15,5	145,10	
	16	17	KCS45 16-240											39	16	17	146,30	
	20	21	KCS45 20-240											39	19	20	148,60	
300	12	13	KCS45 12-300	3	24,5	45	44	13	14	234,30	1	30						
	16	17	KCS45 16-300											45	16	17	238,90	
400	12	13	KCS45 12-400	3,5	27	49	44	24	24	338,70	1	34	GU625					
	20	21	KCS45 20-400											49	24	24	334,10	

Production on request. - Terminals of dimensions other than in chart.