

# EM RANGE

## EM050

Rotary handle  
Thermal protection  
Not suitable for outdoor use  
EM50: without connector  
EM50P: 3 sockets  
2P+E 16A/230V with Protective cover  
(the connection must be made by a professional)



## EM060



## EM100 - EM100R



## EM230 - EM230R



## EM320



Model Code	Old code	Space requirement	Weight	Ø of flanges	Ø of the drum	Useful width	Plugs	Wheels	Material	Indicative capacity based on cable Ø					
										5 mm	7 mm	10 mm	15 mm	20 mm	30 mm
EM050	-	I280xP185x H360 mm	1,7 kg	280 mm	105 mm	90 mm	-	-	Plastic coated galvanised steel frame and flanges	70 m		50 m	20 m		
EM050P	-						4 sockets 2P-E	-		70 m		50 m	20 m		
EM060	EM22	I280xP190x H365 mm	1,2 kg	275 mm	100 mm	105 mm	-	-	Steel frame, plastic drum		100 m	60 m	30 m		
EM100	EM23SR	I550xP380x H625 mm	17 kg	475 mm	250 mm	290 mm	-	-	Epoxy finish steel frame and flanges			100 m	57 m	42 m	21,5
EM100R	EM23				250 mm	290 mm	-	Delivered with 4 casters Ø 80 mm				100 m	57 m	42 m	21,5
EM230	EM25	I540xP440x H465 mm	13,85 kg	398 mm	150 mm	350 mm	-	-				230 m	150 m	80 m	36 m
EM230R	EM25R		16,35 kg		150 mm	350 mm	-	Delivered with 4 casters Ø 100mm, of which 2 with locking mechanism				230 m	150 m	80 m	36 m
EM320	EM26	I680xP440x H465 mm	14,4 kg	395 mm	147 mm	485 mm	-	-				320 m	210 m	120 m	52 m
EM320R	EM26R		16,9 kg		147 mm	485 mm	-	Delivered with 4 casters Ø 100mm, of which 2 with locking mechanism				320 m	210 m	120 m	52 m



# CABLE EQUIPEMENTS

Enrouleurs - Dérouleurs - Métreuses - Protège-câbles

21 rue Sadi Carnot 94880 NOISEAU (France)

Tel : (33) 01 45 90 14 14

Fax : (33) 01 45 90 17 17

contact@cable-equipements.com



### MANUTENTION DES CABLES



### ALIMENTATIONS ELECTRIQUES



### PROTECTION DES CABLES



### FILAGE - TIRAGE



[www.cable-equipements.com](http://www.cable-equipements.com)