



Roxtec H UG™ seal

The Roxtec H UG™ is a three-part seal for easy installation. The transit has a +5mm tolerance towards the aperture and an indicator showing when a compressed seal is achieved.

- For cables in trefoil formation
- Can be used together with Roxtec UG™ sleeve products



ARWI6833_mod.tif

With core

Product	Number of cables/pipes	For cable/pipe Ø (mm)	Aperture dimension Ø (mm)	Weight (kg)	Art. No
H3-135 UG	3	23 - 43	135 - 140	2.2	126281
H3-150 UG	3	24 - 52	150 - 155	2.5	151561
H3-150 UG INSERTABLE	3	24 - 52	150 - 155	2.6	155189
H3-185 UG	3	48 - 64	185 - 190	3.9	126283
H3-200 UG	3	48 - 68	200 - 205	4.3	117842
H3-200 UG INSERTABLE	3	48 - 68	200 - 205	4.2	127053

Without core

Product	Number of cables/pipes	For cable/pipe Ø (mm)	Aperture dimension Ø (mm)	Weight (kg)	Art. No
H3-150 UG INSERTABLE WOC	3	24 - 52	150 - 155	2.3	166396
H3-150 UG WOC	3	24 - 52	150 - 155	2.6	155188
H3-185 UG WOC	3	48 - 64	185 - 190	3.5	151308
H3-135 UG WOC	3	23 - 43	135 - 140	2.3	151306
H3-200 UG INSERTABLE WOC	3	48 - 68	200 - 205	3.7	164807

Product	Number of cables/pipes	For cable/pipe Ø (mm)	Aperture dimension Ø (mm)	Weight (kg)	Art. No
H3-200 UG WOC	3	48 - 68	200 - 205	3	108697