



Roxtec HD transits

High cable density transit devices with frame in 316L.

The Roxtec HD transits are cable entry devices for harsh and hazardous environments that allows up to 32 cables per opening, and are available in two different sizes. The cable transit has a 316L stainless steel frame and sealing modules which are adaptable to a variety of cable sizes. The entry seal can be used with armored cable requiring bonding and grounding.

- Watertight
- Dust-tight
- Rodent resistant
- Corrosion resistant
- Area efficient
- Allows pre-terminated cables



Product	Configuration	External dimensions WxHxD (mm)	Aperture dimensions WxHxD (mm)	Weight (kg)	Art. No
HD 16/4	4x (9.5-31.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	1.6	193101
HD 16/16	16x (3.5-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	1.6	193100
HD 16/10	2x (9.5-31.5), 8x (3.5-15.5)	83.8 x 236 x 60	64(+1/-0.5) x 216(+1/-0.5)	1.6	198297
HD 32/8	8x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	112276
HD 32/20	16x (3.5-15.5), 4x (9.5-31.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	112278
HD 32/32	32x (3.5-15.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.4	112279
HD 32/41	1x (9.5-31.5), 16x (3.5-15.5), 24x (3.0-9.5)	130 x 236 x 60	110(+1/-0.5) x 216(+1/-0.5)	3.3	112280
HDLC/24+2	2x (24.0-54.0), 24x (3.5-16.5)	378 x 120 x 94	366(+1/-1) x 108(+1/-1)	5.6	173277